

GB784 - Twin Disc

STATUS

Reserved

REF. NUMBER

GB784

MANUFACTURE

Twin Disc

TYPE

MG 509

RED.

3,39:1

FABRIKS NR.

Serie 564048 Spec. S-1977



MODEL NO.

MG-505

SPEC. NO.

S-1977

RATIO

3.5:1

SERIAL NO.

67648

TWIN DISC

MARINE REVERSE GEAR

OIL CAPACITY 2.8 GALS MIN OIL PRESS CRUISING 165-PSI

LUBRICATION: USE HEAVY DUTY TYPE ENGINE OIL S.A.E. 30 VISCOSITY WHEN COOLING WATER IS ABOVE 85°F. AND S.A.E. 20 WHEN 85°F. AND BELOW.

EVERY 10 HOURS OR DAILY: CHECK OIL LEVEL.

EVERY 100 HOURS OR WHEN BOAT IS DOCKED: LUBRICATE COUNTERSHAFT SEALS WITH WATER PUMP GREASE TO PREVENT BILGE WATER ENTERING CASE.

EVERY 1000 HOURS: DRAIN, FLUSH AND REFILL CASE WITH CLEAN OIL, REMOVE AND REPLACE FILTER ELEMENT.

NOTE: WHEN TROLLING, OPERATE ACCORDING TO INSTRUCTIONS IN MAINTENANCE MANUAL.

IMPORTANT: WARRANTY IS VOID UNLESS GEAR IS LUBRICATED AND MAINTAINED AS SPECIFIED IN THE MAINTENANCE MANUAL, AVAILABLE ON REQUEST.

SPECIFICATION NO. MUST BE GIVEN WHEN ORDERING PARTS.

CUSTOMER NO. _____

TWIN DISC INTERNATIONAL S.A.
NIVELLES - BELGIUM

U.S. PAT. N°S. 2,779,328 - 2,851,895 - BELGIAN PAT. N° 570,994 - P. 147

MADE IN BELGIUM