

M2347 - ABB

STATUS

Available

REF. NUMBER

M2347

MANUFACTURE

ABB

TYPE

AMA 500L 6L BAFMH

ENGINE NO.

4596464

HP

2010

RPM

1201

YEAR

2008

REMARKS

Unused electro propulsion





ABB		CE		ABB Oy Made in Helsinki, Finland	
Type	AMA 500L6L BAFMH	No	4596464		
Year	2008	Phases	3~	Duty	S1
Connection D	Insul.cl. F	Weight	5340 kg		
IP	S5	IC	81W	IM	1001
S1 CONVERTER SUPPLY, ACS					
0	- 1500				kW
0	- 660				V
0	- 1535				A
0	- 0.88				PF
0	- 60.4				Hz
0	- 1201.3				rpm
Amb. 45°C					
Cooling water temp. 38°C					
Cooling water flow 7.6 m³/h					
IEC 60034-1					
DRIVE END (DE) BEARING		6330/C3			
NON DRIVE END (NDE) BEARING		6324/C3			
LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE		6600	DUTY HOURS		
QUANTITY OF GREASE	DE	100	GRAMS	NDE	100 GRAMS
NOTE: EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.					
NOTE: ABOVE 85°C (185°F) HIGH TEMPERATURE GREASE SHALL BE USED.					
DELIVERED FROM FACTORY WITH GREASE		ES50 UNIREX H2			
FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL					

