






Support types


	C				D			F			P				S					
	1				1 2 3			1 2 3			1 2 3 4				1 2 3 4 5 6					
	MS18																			
	MSE18																			
	A	B	C	D	E	N	Wheel rim mountings	L												
	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]		mm [in]												
 1 2 3 4 P	Ø 175,7 [6,92 dia.]	Ø 225 [8,86 dia.]	Ø 265 [10,43 dia.]	253,45 [9,98]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	10 x M22x1.5	14 [0,55]												
 1 2 3 4 P	Ø 220,7 [8,69 dia.]	Ø 275 [10,83 dia.]	Ø 314 [12,36 dia.]	253,25 [9,97]	Ø 334 [13,15 dia.]	Ø 22 [0,87 dia.]	8 x M20x1.5	14 [0,55]												
 1 2 3 4 P	Ø 220,7 [8,69 dia.]	Ø 275 [10,83 dia.]	Ø 314 [12,36 dia.]	253,25 [9,97]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	12 x M22x1.5	18 [0,71]												
 1 2 3 4 P	Ø 175,7 [6,92 dia.]	Ø 225 [8,86 dia.]	Ø 276 [10,87 dia.]	208,75 [8,22]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	10 x M22x1.5	14 [0,55]												
 1 2 3 4 P	Ø 220,7 [8,69 dia.]	Ø 254 [10,00 dia.]	Ø 285 [11,22 dia.]	163,2 [6,43]	Ø 334 [13,15 dia.]	18 x M16x1.5	-	15 [0,59]												
 1 2 3 4 P	Ø 280,7 [11,05 dia.]	Ø 335 [13,19 dia.]	Ø 382 [15,04 dia.]	292,2 [11,50]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	10 x M22x1.5	25 [0,98]												
 1 2 3 4 P	Ø 175,7 [6,92 dia.]	Ø 225 [8,86 dia.]	Ø 265 [10,43 dia.]	208,75 [8,22]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	10 x M22x1.5	16,5 [0,65]												
 1 2 3 4 P	Ø 220,7 [8,69 dia.]	Ø 275 [10,83 dia.]	Ø 314 [12,36 dia.]	208,8 [8,22]	Ø 334 [13,15 dia.]	Ø 22 [0,87 dia.]	8 x M20x1.5	18 [0,71]												
 1 2 3 4 P	Ø 280,7 [11,05 dia.]	Ø 335 [13,19 dia.]	Ø 385 [15,16 dia.]	301,0 [11,85]	Ø 334 [13,15 dia.]	Ø 24 [0,94 dia.]	10 x M22x1.5	14 [0,55]												



The supports in gray must not be assembled with an MSE hydrobase.

Studs

		P	C min.	C max.	D	Class
		mm [in]	mm [in]	mm [in]	mm [in]	
Various studs	M16 x 2	50 [1.97]	5 [0.20]	17,75 [0.70]	21 [0.83]	12.9
	M20 x 1.5	60 [2.36]		20 [0.79]	25 [0.98]	
	M20 x 1.5	70 [2.76]		27 [1.06]	25 [0.98]	
	M22 x 1.5	65 [2.56]		24 [0.94]	26 [1.02]	
	M22 x 1.5	80 [3.15]		29 [1.14]	26 [1.02]	
Screws	M16 x 1.5	-	-	-	-	10.9
	M20 x 1.5	-	-	-	-	



See generic installation motors N°B59689D.